

Acromul® 425ES

Edition 9-2018

Acromul® 425ES is a 45% solids content Styrene Acrylic copolymer water-dispersion containing anionic surfactants.

Stabilizer: Surfactants

1. SUPPLY SPECIFICATIONS

• Solid content	45.0 ± 1.0%
• Brookfield viscosity	6,000 ± 2,000
• pH	8.0 ± 1.0

2. TYPICAL VALUES

• Minimum film-forming temperature	16.0 ± 1.0
• Prevailing particle size range	0.2 ± 0.1 Microns
• Dispersing system	anionic - non ionic
• Density at 23°C	1.04
• Mechanical stability	Excellent

APPLICATIONS

Indoor and outdoor water based paints and wall textured coatings and primers.

SPECIFIC PROPERTIES

Acromul® 425ES is a fine particle size Styrene Acrylic Emulsion, supplied at 50% solids content for the formulation of interior and exterior emulsion paints, primers, undercoats, putties, etc. to be applied on mineral substrates such as masonry, plasters, fibre cement and concrete.

ACROMUL® 570W, demonstrates wide formulation latitude from gloss through semi-gloss to matt paints with a markable washability range, which is suitable for both interior and exterior applications. The hardness level of this binder makes Acromul® 425ES suitable for miscellaneous applications such as interior undercoats and wall paints making it a truly general purpose or so called "universal" binder for paint companies wishing to minimise the number of raw materials.

PACKAGING

Acromul® 425ES is available in bulk and in IBC's, 160kg, 150kg, 125 Kg or 50 Kg drums.

STORAGE

Acromul® 425ES is stable for at least 12 months when stored between +5°C and +40°C.

Egyptian British Company maintains Material Safety Data sheets (MSDS) on all of its products. These contain important information that you may need to protect your employees and customers against any known health and safety hazards associated with our products. We recommend you to obtain copies of MSDS for our products, from our technical representative, and obtain copies of MSDS from your suppliers of other raw materials used with our products.