

Sunovad[®] 200SFK

Edition 9-2018

Sunovad[®] 200SFK is a silicon free defoamer for water based paints and inks

Stabilizer: Surfactants

APPLICATIONS

Indoor and outdoor water based paints and wall textured coatings and primers.

SPECIFIC PROPERTIES

Sunovad[®] 200SFK, is highly recommended for high gloss and industrial coating, silk and gloss emulsion paints, inks and overprint varnishes and adhesives as one of the high efficient defoamers for emulsion paints with excellent spreading capability, thermal stability, chemical inertness and water insolubility

Dose in general is a ratio from 0.1 to 1.0 % calculated on the total quantity of paint formulation

PACKAGING

Sunovad[®] 200SFK is available in bulk and in IBC's, 160kg, 150kg, 125 Kg or 50 Kg drums.

STORAGE

Sunovad[®] 200SFK is stable for at least 12 months when stored between +5°C and +40°C.

Egyptian British Company maintains Material Safety Data sheets (MSDS) on all of its products. These contain important information that you may need to protect your employees and customers against any known health and safety hazards associated with our products. We recommend you to obtain copies of MSDS for our products, from our technical representative, and obtain copies of MSDS from your suppliers of other raw materials used with our products.

All rights reserved for Egyptian-British Co.